

Are your electronic files getting out of control? Consolidate and manage your electronic data in an affordable, compact storage device.



- 640 GB, 1.0 TB, 1.6 TB and 2.0 TB models
- 4 hot-swap SATA 1.5 Gb/s high-capacity disk drives
- 18 – 22 MB/sec performance
- Intel® xScale® processor with Linux® based operating system for reliability and compatibility
- Two USB ports on the front panel for easy connection with digital media devices; both can be configured for separate networks or direct connect
- Two GigE RJ45 Ethernet ports on the rear panel for direct-attach or Ethernet-based host connection
- Locking front and rear panels for added security against unauthorized removal of hot-swap drives
- Supports Active Directory Services

The Future of Networked Storage – Today.

Is your electronic data getting too big to handle? Now there's an easy, affordable solution for consolidating and managing your electronic files – the Hammer™ NA-1400 Network-Attached Storage Appliance. The NA-1400 connects to your network, personal computer or favorite media device to provide up to two terabytes of external storage in a compact, external unit.

For your small business, you can use the NA-1400 as a repository for your shared data, a backup center for critical user data or as an incremental storage unit. Or, if you need extra data storage at home, you can use the NA-1400 as a storage center for files from all your USB 2.0-compliant electronic home media devices – including MP3 players, digital cameras, PDAs, laptop and desktop computers, DVD players/recorders and set-top boxes.

Plus the NA-1400 is easy to use. Pre configured with user-friendly software, the NA-1400 guides you through installation, maintenance and management activities as you integrate additional storage to your home or business computing environment. The NA-1400 also features two USB ports on the front panel and two GigE ports on the rear panel for easy connectivity.

The NA-1400 is ideal for:

Small Businesses Store and protect important business data in your branch office or small business.

Home Media Safeguard your personal data, video, photos, movies and music.

Data Protection Use as a printer server or backup device and enjoy full-featured data protection.

NA-1400

Models and Accessories



- NA-1400 640GB (4 x 160GB SATA 1.5 Gb/s drives, preconfigured)
- NA-1400 1.0TB 4 x 250GB SATA 1.5 Gb/s drives, preconfigured)
- NA-1400 1.6TB (4 x 400GB SATA 1.5 Gb/s drives, preconfigured)
- NA-1400 2.0TB (4 x 500GB SATA 1.5 Gb/s drives, preconfigured)

Hammer NA-1400 Network Attached Storage Appliance

- Up to 2 TB of RAID 5 storage.
- Affordable repository for shared data, backup center for critical data or incremental storage unit.
- Easy-to-use, easy-to-install and pre-configured with user friendly software.
- 4 hot-swap SATA 1.5 Gb/s high-capacity disk drives
- 18–22 MB/sec performance
- Intel® xScale® processor with Linux®-based operating system for reliability and compatibility
- Two USB ports on the front panel for easy connection with digital media devices; both can be configured for separate networks or direct connect
- Two GigE RJ45 Ethernet ports on the rear panel for direct-attach or Ethernet-based host connection
- Locking front and rear panels for added security against unauthorized removal of hot-swap drives

World-class technical support

Hammer Storage
1941 Ringwood Ave
San Jose, CA 95131
www.hammer-storage.com
info@hammer-storage.com
888-444-9977



Copyright 2006. All rights reserved. The Hammer Storage logo is a trademark of Bell Microproducts. NEWISYS® is a registered trademark of NEWISYS®, Inc. NEWISYS® and its logo are trademarks of NEWISYS®, Inc. NEWISYS®, Inc. is a Sanmina-SCI company. All other product names used in this publication are for identification purposes only and may be trademarks of their respective owners.

Technical Specifications

DESCRIPTION	
Model Name	Hammer NA-1400
Form Factor	Desktop
CAPACITY AND INTERFACE	
Enclosure Capacity	Up to 2 TB
Network Interface	Two 1Gb Ethernet RJ45 connectors located on the rear panel. Two USB 2.0 connectors located on the front panel.
Memory	Single 256MB DDR SDRAM w/ECC, expandable to 512MB
Cache	32KB data cache.
Processor	Intel® XScale® 80219 600 MHz Processor.
RAID Constructs	0, 1 and 5
COMPATIBILITY	
Operating Systems	Microsoft® Windows® 9.X, Windows ME, Windows 2000, Windows 2000 Server, Windows XP Professional, Windows XP Home Edition, RedHat®, Mandrake®, SUSE®.
File Systems	SMB, CIFS, XFS, HTTP, CIM Client, Anonymous FTP.
PERFORMANCE	
Single Enclosure Performance	18-22MB/sec.
Aggregated Enclosure Performance	Limited only by the maximum bandwidth of aggregating switches.
PHYSICAL DIMENSIONS	
H x W x L (in)	8.7 x 7.2 x 10.2
H x W x L (mm)	220 x 170 x 260
Weight (lbs / kg)	7.9/3.6
POWER REQUIREMENTS	
Output	12V, 10.8A, 130W max.
Input	90 – 264VAC, 47 – 62 Hz, 3.2A @ 115VAC, 1.7A @ 230VAC.
ENVIRONMENTAL	
Operating Temperature	0 to 40 deg C
Operating Humidity	8% to 80% (non-condensing)
Operating Shock	5G, 11ms
Non-Operating Shock	30G, 11ms
Operating Vibration	0.25G at 5Hz to 500Hz
Non-Operating Vibration	10G at 5Hz to 500Hz
Safety and Agency	FCC Class B